imageCLASS

-

Canon

Delighting You Always

SOUTH & SOUTHEAST ASIA REGIONAL HEADOUARTERS

Canon Singapore Pte. Ltd. 1 HarbourFront Avenue #04-01 Keppel Bay Tower Singapore 098632 Tel: 65-6799-8888 Fax: 65-6799-8882

www.canon-asia.com

CANON OFFICES

HONG KONG Canon Hongkong Co., Ltd. Tel: 852-3191-2388 Fax: 852-2369-3800 www.canon.com.hk

INDIA

Canon India Pvt. Ltd. Tel: 91-124-4160-000 Fax: 91-124-4160-011 www.canon.co.in

MALAYSIA

Canon Marketing (Malaysia) Sdn. Bhd. Tel: 603-7844-6000 Fax: 603-7845-0505 www.canon.com.my

PHILIPPINES

Canon Marketing (Philippines), Inc. Tel: 632-884-9000 Fax: 632-894-4174 www.canon.com.ph

SINGAPORE

Canon Singapore Pte. Ltd. Tel: 65-6799-8888 Fax: 65-6799-8882 www.canon.com.sg

THAII AND

Canon Marketing (Thailand) Co., Ltd. Tel: 66-2-3449-999 Fax: 66-2-3449-967/68 www.canon.co.th

VIETNAM

Canon Marketing Vietnam Co., Ltd. Ho Chi Minh City, Vietnam Tel: 84-8-38200-466 Fax: 84-8-38200-477 www.canon.com.vn

CANON BUSINESS PARTNERS

BANGLADESH J.A.N. Associates Tel: 880-2-8611-444 Fax: 880-2-8610-410

BRUNEI

Interhouse Company Tel: 673-2-6530-01 Fax: 673-2-6530-03

CAMBODIA i-Olick (Cambodia) Pte. Ltd. Tel: 855-23-9966-38 Fax: 855-23-9966-39

INDONESIA

PT Datascrip Tel : 62-21-29226000 Fax : 62-21-6544811-13

MALDIVES SIMDI Company (Pvt) Ltd. Tel: 960-3334-421 Fax: 960-3334-424

MYANMAR

Mvanmar Golden Rock International Co. Ltd. Tel: 95-1-654810 Fax: 95-1-654820

NEPAL

International Electronics Concern (P) Ltd. Tel: 977-1-4421-991 Fax: 977-1-4421-909

PAKISTAN

MBM International Tel: 9221-3227-0933 Fax: 9221-3438-6308

SRI LANKA

Metropolitan Computers (Pvt) Ltd. Tel: 94-11-2437-797 Fax: 94-11-2448-980



DEALER'S STAMP

175W597 © 2013 Canon Singapore Pte. Ltd. All rights reserved.

his document is for information purpose only and the contents are subject to change without notice. Product options, name ind availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any ability or contractual obligations with respect to this document.

Canon, imageCLASS, MEAP, Business Can Be Simple and Get Smart Get Genuine are trademarks of Canon Inc. and/or its ffiliates. Other names may be the trademarks of their respective owners

iniFLOW is an independent party software distributed by Canon Singapore Pte. Ltd.

>> 40ppm (A4) >> First Printout in 8.6 secs >> Gigabit Ethernet >> Automatic Duplex

>> 768MB device memory >> Direct PDF printing >> Energy Saving



-

imageCLASS

OUTSTANDING PRINT PERFORMANCE WITH LOWER COST **OF OPERATION**

Powered by one of the fastest print engines in the Canon single-function printer lineup, the imageCLASS LBP678Dx stands tall against a backdrop of high-performance office equipment. A large paper input capacity with the option of a high-yield toner cartridge minimizes the need for frequent paper and toner replacements, while Direct PDF printing using USB flash memory allows standalone operation without a PC. With the ability to accept up to two additional paper cassettes, the LBP6780x is designed to satisfy even the most print-hungry of office environments.

EXCELLENT PRINT PERFORMANCE

Churn out high-guality monochrome documents at up-to 40ppm (A4), aided by a First Printout Time of just 8.6 seconds.

QUICK RESPONSE TIME

The LBP6780x springs to life in just 10 seconds when called into action, even after long periods of inactivity. This is made possible by Canon's proprietary On-Demand Fixing technology which transfers heat directly to the heating element, producing impressive device warm-up and recovery times.





Fixing


• •

0000/

Image Surface

0000





Heating entire roller surface results in longer warm-up time and higher power consumption

Heat transferred directly to fixing film reduces warm-up time and saves energy



*LBP6780x with an optional paper feeder installed

HIGH OUALITY PRINTING

Enjoy razor-sharp text and images at up to 1200 x 1200 dpi (equivalent), or 2400 (equivalent) x 600 dpi print resolution.

AUTO DUPLEX PRINT

Reduce paper usage and expenses by making use of the automatic duplex printing and multiple layout options.

SUPPORTS MULTIPLE PRINT LANGUAGES

Canon UFR II technology utilizes Load Balancing Technology to speed up print job processing, thus reducing reliance on costly device memory upgrades. PCL5e/PCL6 and genuine Adobe PostScript 3 are also included as standard print languages, allowing the LBP6780x to be configured easily for different operating environments.



F

Auto Duplex Print

SUPPORTS HIGH-VOLUME PRINTING

Equipped with a standard 500-sheet cassette and a 100-sheet multipurpose tray, the LBP6780x is ideal for high-print volume Paper Feeder environments. Two optional 500-sheet cassette feeders can be added to increase the input capacity to a maximum of 1,600 sheets.

DIRECT PRINTING FROM USB STORAGE

Increase document printing mobility by simply printing TIFF, JPEG, PDF, and XPS files direct from a USB storage device, without the need for a PC. **PDF XPS**



LOW MAINTENANCE

imageCLASS

L B P 6 7 8 0 x

Enjoy fuss-free and low maintenance operation with the All-in-One Cartridge 324 design. The printer is also compatible with the higher-capacity Cartridge 324 II, allowing a longer period of device operation before requiring toner replacement.

Cartridge 324 GENUINE

ADVANCED NETWORK CAPABILITIES

With built-in Gigabit Ethernet connectivity, data transfer speeds of up to 1000 Mbits/sec can be supported.



BUILT-IN MEAP - COMPATIBLE WITH THE UNIFLOW SOLUTION

Canon Multifunctional Embedded Application Platform, or MEAP, is an application development platform that allows JAVA applications to be embedded within supported devices. The LBP6780x is a MEAP-enabled single-function printer that integrates seamlessly into the uniFLOW architecture, allowing server-based secure print management and advanced cost-accounting features. The LBP6780x is also able to connect directly to a MiCard reader to enable secure print job release via pre-configured ID security cards.

DOCUMENT SECURITY & COST CONTROL

Designed to help manage the office's document output, uniFLOW also incorporates secure printing functionality, intelligent rules-based print-routing for cost efficiency, and maximum print availability.

With uniFLOW you are able to determine which persons in your organisation are accountable for various print jobs



Secure Print

F

OPTIONAL SD CARD B-1 FOR SECURE DOCUMENT PRINTING

For smaller offices, the LBP6780x also offers an affordable server-less secure print solution with great ease-of-use. The optional Canon SD Card-B1 accessory is required to activate this feature.

LOW POWER CONSUMPTION

The LBP6780x draws a minimal 1W power in Sleep Mode, and carries an Energy Star TEC (Typical Electricity Consumption) value of 1.9kWh/week, making it one of the most energy-efficient printers in its class.

Canon EF-Toner has low-melting point and firm-fixing characteristics to enhance the On-Demand Fixing process, resulting in fast recovery time from Standby mode and overall lower power consumption.





ENERGY-SAVING FINE TONER



SPECIFICATIONS

imageCLASS LBP6780x

Printing Method		Black & White Laser Beam Printing
Fixing Method		On-Demand Fixing
Print Speed	Mono: A4/Letter	40/42ppm
	Duplex: A4/Letter	20/20.5ppm (10/10.25spm; sheets/min)
Print Resolution		600 × 600dpi 1200 x 1200dpi (equivalent) 2400 (equivalent) × 600dpi
First Printout Time (FPOT)		8.6/8.5 secs (A4 / Letter)
Warm-Up Time (From Power On)		28 secs or less
Recovery Time (From Sleep Mode)		Sleep Mode 1 (Panel OFF): 0 sec Sleep Mode 2 (Engine Sleep): 10 secs Sleep Mode 3 (Deep Sleep): 10 secs
Page Description Language		PCL5e/6, UFR II, PostScript 3, PDF, XPS
Paper Input (Based on 64g/m²)	Standard Cassette	500 sheets
	Multi-Purpose Tray	100 sheets
	Optional Paper Feeder (PF-45)	500 sheets (max. 2 trays)
	Maximum Paper Capacity	1,600 sheets
Paper Output (Based on 64g/m²)	Face-Down	250 sheets
	Face-Up	50 sheets
Paper Size	Standard Cassette	A4 / B5 / A5 / A6 / Legal / Letter / Executive / 16K / 8.5"×13" / Custom sizes (Width: 105.0 - 215.9mm x Length: 148.0 - 335.6mm)
	Multi-Purpose Tray	A4 / B5 / A5 / A6 / Legal / Letter / Executive / 16K / 8.5"×13" / Custom sizes (Width: 76.2 - 215.9mm x Length: 127.0 - 355.6mm)
	Optional Paper Feeder (PF-45)	A4 /B5 / A5 / A6 / Legal / Letter / Executive / 16K / 8.5"×13"/ Custom sizes (Width: 105.0 - 215.9mm x Length: 148.0 - 355.6mm)
Paper Weight	Standard Cassette	60~120g/m²
	Multi-Purpose Tray	60~199g/m²
	Optional Paper Feeder (PF-45)	60~120g/m²
Paper Type		Plain Paper / Heavy Paper / Transparency / Label / Index Card / Envelope
Paper Margins		5mm - top, bottom, left and right (Envelope: 10mm)
Duplex Printing		Standard (only A4 / Letter / Legal / 8.5"×13") (Paper Weight: 60-120g/m²)
Standard Interfaces	USB	USB 2.0 High Speed, USB 2.0 Host (2 ports)
	Network	10Base-T / 100Base-TX / 1000Base-T
	Expansion Interface	SD Card Slot x 1
Compatible Operating Sy	rstems	Windows XP (32bit/64bit), Windows Server 2003 (32bit/64bit), Windows Vista (32bit/64bit), Windows Server 2008 R2 (64bit), Windows Server 2008 (32bit/64bit), Windows 7(32bit/64bit), Mac OS X 10.5.8 and above*1, Linux*2, Citrix
Device Memory		768MB
Optional ROM		Barcode Printing Kit-F1
Standard Fonts		93 Scalable, 136 PostScript Fonts
SD Card (Option)		Canon SD Card-B1 (8GB)
Operation Panel		5 Line LCD
Noise Level*3	During Operation	54.5dB or less (Sound Pressure Level) / 7.3B or less (Sound Power Level)
	During Standby	Inaudible (Sound Pressure Level) / Inaudible (Sound Power Level)
Power Consumption	Maximum	1,400W or less
	During Operation	Approx. 660W
	During Standby	Approx. 15W
	During Sleep	Sleep Mode 1 (Panel OFF): Approx. 15W Sleep Mode 2 (Engine Sleep): Approx. 5.4W Sleep Mode 3 (Deep Sleep): Approx. 1.0W
Energy Star TEC (Typical	Electricity Consumption)	1.9kWh/week
Dimensions (W×D×H)		454 x 424 x 345mm
Weight		Approx. 16.6kg (Without Cartridge)
Power Requirements		AC 220-240V(±10%), 50/60Hz(±2Hz)
Power Requirements Operating Environment		AC 220-2400(±10%), 50/60H2(±2H2) Temperature: 10~30°C / Humidity: 20~80%RH (No Condensation)
Toner Cartridge [*] 4		Cartridge 324: 6,000 pages
-		Cartridge 324 II: 12,500 pages*5

The latest drivers for Mac OS can be downloaded from www.canon-asia.com when available

- The latest drivers for Linux can be downloaded from www.canon-asia.com when available
- fested in accordance to ISO7779 and declared per 509296

Foner cartridge yield in accordance with ISO/IEC 19752

- The LBP6780x is bundled with Cartridge 324, and is also compatible with Cartridge 324 II. Cartridge 324 II is suitable for users with higher print volume
- Monthly Duty Cycle value provides a means for omparison of product obustness in relation to other anon Laser Devices, and does not refer to actual maximum mage output per month