

## imageRUNNER ADVANCE C5500 III Series

Color | Mid-volume | Multifunction

Print up to 60 ppm (BW/color)

Scan up to 160 ipm (300 dpi) (BW/color, duplex)

Print up to 12" × 18"

6,350-sheet maximum paper capacity



Canon's comprehensive portfolio of imageRUNNER ADVANCE multifunction printers and integrated solutions can help **simplify** the end user experience and management of technology, better **control** sensitive information and print-related costs, and help ensure that technology investments proactively **evolve** with changing needs.



### WORKFLOW EFFICIENCY

- 10.1" intuitive touchscreen with smartphone-like usability.
- A unique, customized experience tailored to individual preferences using My ADVANCE.
- Supports mobile solutions and integration with many popular cloud services like Google Drive!
- Scan and convert documents to searchable digital files in a variety of file formats.
- Integration with Canon and various third-party software with embedded application platform.



### SECURITY

- Advanced standard security feature set to help safeguard sensitive information and assist in regulatory compliance.
- Integrates with existing, third-party Security Information and Event Management (SIEM) systems to help provide real-time comprehensive insights into potential threats to the network and printers.
- Technology to verify that the device boot process, firmware, and applications initialize without alterations or tampering.
- Security policy settings can be controlled with a dedicated password, configured from a central location, and exported to other supported devices.
- Control access to the device and specific features, using a host of flexible authentication methods—PIN code, user name/password, or card access.<sup>2</sup>



### QUALITY AND RELIABILITY

- Canon's signature reliability and engine technologies help keep productivity high and minimize the impact on support resources.
- Outstanding imaging technologies and toner allow for consistently striking images, thanks to Canon's V<sup>2</sup> color profile.
- Designed to achieve maximum uptime with status notifications that help keep supplies replenished and intuitive maintenance videos for consumables replacement.
- imageRUNNER ADVANCE models have received many awards and recognition from leading industry analysts, often referencing strong reliability.



## DEVICE AND FLEET MANAGEMENT

- Designed for quick, easy deployment.
- Remote diagnostics and parts life management for proactive maintenance and rapid fixes.
- Easy and intuitive to monitor device status and consumable levels, turn off devices remotely, observe meter readings, manage settings, and implement security policies.
- Common firmware and regular updates with Unified Firmware Platform (UFP) for continuous improvements and consistency across a fleet.



## COST MANAGEMENT

- Track and assess print, copy, scan, and fax usage and allocate costs to departments or projects.
- Apply print policies and restrict usage by user to help reduce unnecessary printing and contribute to cost efficiency.
- Standard cloud-based solution provides a centralized dashboard with up-to-the-minute insights into printer activity.
- Upgrade to uniFLOW server or cloud-based solutions for full accounting and reporting for compatible Canon and third-party devices, pull printing, job routing, and powerful scan workflows.



## SUSTAINABILITY

- A combination of fusing technologies and low-melting-point toner minimizes power requirements and helps achieve low energy consumption.
- Encourage environmentally conscious work practices by enabling multiple settings that can help save paper and energy.
- ENERGY STAR® certified and rated EPEAT® Gold.<sup>3</sup>

## CONFIGURATION OPTIONS



### STAPLE FINISHER-Y1

- 2-tray, 3,250-sheet capacity
- Corner and double stapling up to 50 sheets
- Supports Staple-free Stapling and Staple On Demand
- Supports optional internal 2/3-hole puncher (2/3 Hole Puncher Unit-A1)



### BOOKLET FINISHER-Y1

- 2-tray, 3,250-sheet capacity
- Corner and double stapling up to 50 sheets
- Booklet-making up to 20 sheets and saddle-folding up to 3 sheets
- Supports Staple-free Stapling and Staple On Demand
- Supports optional internal 2/3-hole puncher (2/3 Hole Puncher Unit-A1)



### INNER FINISHER-HI

- 2-tray, 545-sheet capacity
- Corner and double stapling up to 50 sheets within the footprint of the main unit
- Supports Staple-free Stapling and Staple on Demand
- Supports optional internal 2/3-hole puncher (Inner 2/3 Hole Puncher-B1)



### INNER 2-WAY TRAY




### HIGH CAPACITY CASSETTE FEEDING UNIT-A1

- 2,450-sheet capacity
- Supports up to Letter
- 14 lb. Bond to 140 lb. Index




### CASSETTE FEEDING UNIT-AM1

- Two 550-sheet cassettes
- Supports up to 12" x 18"
- 14 lb. Bond to 140 lb. Index



### UTILITY TRAY-B1



### COPY TRAY-J2



### PAPER DECK UNIT-F1

- 2,700-sheet capacity
- 14 lb. Bond to 140 lb. Index
- Supports Letter



### imagePASS-P2

- Delivers fast processing speed, outstanding image quality, and time-saving workflow
- Personalized printing with the built-in, entry-level Fiery FreeForm™ or with the supported variable data printing (VDP) formats

# SPECIFICATIONS

## Main Unit

### Type

Color Laser Multifunctional

### Core Functions

Standard: Print, Copy, Scan, Send, Store  
Optional: Fax

### Processor Speed

Canon Dual Custom Processor (Shared)

### Control Panel

10.1" TFT LCD WSVGA Color Flat-panel

### Memory

4.0 GB RAM

### Hard Disk

Standard: 250 GB/Maximum: 1 TB

### Interface Connection

Network: 1000Base-T/100Base-TX/10Base-T,  
Wireless LAN (IEEE 802.11 b/g/n)

### Others

Standard: USB 2.0 x2 (Host), USB 3.0 x1 (Host),  
USB 2.0 x1 (Device)  
Optional: Serial Interface, Copy Control Interface

### Paper Output Capacity (LTR, 20 lb. Bond)

Standard: 250 Sheets  
Maximum: 3,450 Sheets  
(with External Finisher and Copy Tray)

### Paper Sources (LTR, 20 lb. Bond)

Standard: Dual 550-sheet Paper Cassettes,  
100-sheet Stack Bypass  
Optional: Dual 550-sheet Paper Cassettes  
(CASSETTE FEEDING UNIT-AM1),  
2,450-sheet High Capacity Paper Cassette  
(HIGH CAPACITY CASSETTE FEEDING  
UNIT-A1), 2,700-sheet Paper Deck  
(PAPER DECK UNIT-F1)

### Paper Capacity (LTR, 20 lb. Bond)

Standard: 1,200 Sheets  
Maximum: 6,350 Sheets

### Finishing Capabilities

Standard: Collate, Group  
With Inner Collate, Group, Offset, Staple, Hole Punch,  
Finisher: Staple-free Staple, Staple On Demand  
With External Collate, Group, Offset, Staple, Booklet, Hole  
Finishers: Punch, Staple-free Staple, Staple On Demand

### Supported Media Types

Paper Thin, Plain, Recycled, Color, Heavy,  
Cassette 1: Pre-punched, Letterhead, Bond,  
Transparency, Envelope  
Paper Thin, Plain, Recycled, Color, Heavy,  
Cassette 2: Pre-punched, Letterhead, Bond,  
Transparency, Tab, Envelope  
Stack Bypass: Thin, Plain, Recycled, Color, Heavy,  
Pre-punched, Labels, Letterhead, Bond,  
Coated, Transparency, Tab, Tracing,<sup>4</sup>  
Envelope

### Supported Media Sizes

Paper Letter, Executive, Statement-R, Envelope  
Cassette 1: [No.10 (COM10), DL, ISO-C5], Custom Size  
(3-7/8" x 5-7/8" to 11-3/4" x 8-1/2")  
Paper 12" x 18", 11" x 17", Legal, Letter, Letter-R,  
Cassette 2: Executive, Statement-R, Envelope  
[No.10 (COM10), Monarch, DL, ISO-C5],  
Custom Size (3-7/8" x 7-1/8" to 12" x 18")  
Stack Bypass: 12" x 18", 11" x 17", Legal, Letter, Letter-R,  
Executive, Statement, Statement-R,  
Envelope [No.10 (COM10), Monarch, DL,  
ISO-C5], Envelope Custom Size (3-7/8" x  
3-7/8" to 12-5/8" x 18"), Custom Size  
(3-7/8" x 5-1/2" to 12-5/8" x 18"), Free Size  
(3-7/8" x 5-1/2" to 12-5/8" x 18")

### Supported Media Weights

Cassettes: 14 lb. Bond to 140 lb. Index (52 to 256 g/m<sup>2</sup>)  
Stack Bypass: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m<sup>2</sup>)  
Duplexing: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m<sup>2</sup>)

### Warm-up Time

From Power On: Approx. 10 Seconds<sup>5</sup>  
From Sleep Mode: Approx. 10 Seconds<sup>6</sup>  
Quick Startup Mode: Approx. 4 Seconds<sup>7</sup>

### Dimensions (W x D x H)

24-3/8" x 29-1/4" x 47-2/7" (620 mm x 742 mm x 1201 mm)<sup>8</sup>

### Installation Space (W x D)

Basic: Stack Bypass + Cassette Drawers open:  
37-1/8" x 46-3/8" (943 mm x 1176 mm)<sup>9</sup>

### Weight

Approx. 310.9 lb. (141kg)<sup>9</sup>

## Print Specifications

### Print Speed (BW and Color)

C5560i III: Up to 60 ppm (Letter); Up to 36 ppm  
(Letter-R); Up to 34 ppm (Legal);  
Up to 32 ppm (11" x 17")  
C5550i III: Up to 50 ppm (Letter); Up to 30 ppm  
(Letter-R); Up to 29 ppm (Legal);  
Up to 27 ppm (11" x 17")  
C5540i III: Up to 40 ppm (Letter); Up to 24 ppm  
(Letter-R); Up to 23 ppm (Legal);  
Up to 22 ppm (11" x 17")  
C5535i III: Up to 35 ppm (Letter); Up to 23 ppm  
(Letter-R); Up to 21 ppm (Legal);  
Up to 18 ppm (11" x 17")

### Print Resolution (dpi)

1200 x 1200, 600 x 600

### Standard Page Description Languages

UFR II, PCL6, Adobe PS 3

### Direct Print

Available from USB, Advanced Box, Remote UI, and  
Web Access<sup>10</sup>

### Supported File Types

PDF, TIFF, JPEG, EPS,<sup>11</sup> XPS

### Printing from Mobile and Cloud-based Services

A range of software and MEAP-based solutions are  
available to provide printing from compatible mobile devices  
or Internet-connected devices and cloud-based services  
depending on your requirements. Please contact your sales  
representative for further information.<sup>12</sup>

### Fonts

PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts,  
Andalé Mono WT J/K/S/T (Japanese,  
Korean, Simplified and Traditional Chinese),<sup>13</sup>  
Barcode Fonts<sup>14</sup>  
PS fonts: 136 Roman

### Operating System<sup>15</sup>

UFR II: Windows Server 2008/Windows 7/Server  
2008 R2/Server 2012/Windows 8.1/Server  
2012 R2/Windows 10/Server 2016, MAC OS  
X (10.9 or later)  
PCL: Windows Server 2008/Windows 7/Server  
2008 R2/Server 2012/Windows 8.1/Server  
2012 R2/Windows 10/Server 2016  
PS: Windows Server 2008/Windows 7/Server  
2008 R2/Server 2012/Windows 8.1/Server  
2012 R2/Windows 10/Server 2016, MAC OS  
X (10.9 or later)  
PPD: MAC OS X (10.3.9 or later), Windows 7/8.1/10

## Copy Specifications

### Copy Speed (BW and Color)

C5560i III: Up to 60 ppm (Letter); Up to 36 ppm  
(Letter-R); Up to 34 ppm (Legal);  
Up to 32 ppm (11" x 17")  
C5550i III: Up to 50 ppm (Letter); Up to 30 ppm  
(Letter-R); Up to 29 ppm (Legal);  
Up to 27 ppm (11" x 17")  
C5540i III: Up to 40 ppm (Letter); Up to 24 ppm  
(Letter-R); Up to 23 ppm (Legal);  
Up to 22 ppm (11" x 17")  
C5535i III: Up to 35 ppm (Letter); Up to 23 ppm  
(Letter-R); Up to 21 ppm (Legal);  
Up to 18 ppm (11" x 17")

### First-Copy-Out Time

C5560i III: As fast as 2.9 seconds (BW)/  
4.5 seconds (Color)  
C5550i III: As fast as 3.5 seconds (BW)/  
5.2 seconds (Color)  
C5540i III: As fast as 4.1 seconds (BW)/  
6.1 seconds (Color)  
C5535i III: As fast as 4.9 seconds (BW)/  
7.4 seconds (Color)

### Copy Resolution (dpi)

Reading: 600 x 600  
Printing: 1200 x 1200

### Multiple Copies

Up to 999

### Magnification

25%-400% (1% Increments)

### Preset Reductions

25%, 50%, 64%, 73%, 78%

### Preset Enlargements

121%, 129%, 200%, 400%

### Basic Copy Features

Preset Reduction/Enlargement Ratios by Area, Paper  
Setting, Previous Settings, Favorite Settings, Finishing,  
Two-sided, Density Adjustment, Original Type Selection,  
Interrupt Mode, Setting Confirmation/Cancel

### Special Copy Features

Book to Two Pages, Two-sided Original, Finishing, Booklet,  
Job Build, N on 1, Add Cover, Insert Sheets, Different-size  
Originals, Density Adjustment, Original Type Selection,  
Transparency Cover Sheets, Page Numbering, Copy Set  
Numbering, Sharpness, Erase Frame, Secure Watermark,  
Print Date, Shift, Gutter, Print & Check, Negative/Positive,  
Repeat Images, Merge Job Blocks, Job Done Notice, Mirror  
Image, Print on Tab, Store in Mail Box, Superimpose Image,  
Copy ID Card, Skip Blank Pages, Detect Feeder Multi Sheet  
Feed, Free Size Original, Color Balance, Adjust One-Touch  
Color, Area Designation

## Scan Specifications

### Type

Color Platen and Single-Pass Duplexing Automatic  
Document Feeder

### Document Feeder Paper Capacity

150 Sheets (20 lb. Bond)

### Document Feeder Supported Media Sizes

11" x 17", Legal, Letter, Letter-R, Statement, Statement-R,  
Custom Size: 5" x 5-1/2" to 12" x 17"

### Document Feeder Supported Media Weights

BW Original: 13 lb. Bond to 58 lb. Cover (50 to 157 g/m<sup>2</sup>)  
Color Original: 17 lb. Bond to 58 lb. Cover (64 to 157 g/m<sup>2</sup>)

### Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects [Height: up to 2"  
(50 mm), Weight: Up to 4.4 lb. (2kg)]

### Pull Scan

Color Network ScanGear2 for both Twain and WIA  
Supported OS: Windows 7/8.1/10  
Server 2008/Server 2008 R2/Server  
2012/Server 2012 R2/Server 2016

### Scan Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200,  
200 x 100, 150 x 150, 100 x 100

### Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to  
compatible mobile devices and certain cloud-based  
services depending on your requirements.

### Scan Speed (Letter)

#### Single-sided Scanning

BW: 80 ipm (300 dpi)/80 ipm (600 dpi)  
Color: 80 ipm (300 dpi)/60 ipm (600 dpi)

#### Double-sided Scanning

BW: 160 ipm (300 dpi)/150 ipm (600 dpi)  
Color: 160 ipm (300 dpi)/80 ipm (600 dpi)

## Send Specifications

### Destination

Email/Internet Fax (SMTP), SMB v3.0, FTP, WebDAV, Mail Box, Super G3 Fax (Optional), IP Fax (Optional)

### Address Book

LDAP (2,000)/Local (1,600)/Speed Dial (200)

### Send Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

### Communication Protocol

File: FTP (TCP/IP), SMB v3.0, WebDAV  
Email: SMTP, POP3

### File Format

Standard: TIFF, JPEG, PDF (Encrypted, Compact, Searchable, Apply Policy, Optimize for Web, PDF A/1-b, Limited Color Device Signature), XPS (Compact, Searchable, Device Signature), Office Open XML (PowerPoint, Word)  
Optional: PDF (Trace & Smooth, User Signature), XPS (User Signature)

### Universal Send Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, Email Priority, TX Report, Original Content Orientation, Skip Blank Originals, Detect Feeder Multi Sheet Feed

## Fax Specifications (Optional)

### Modem Speed

Super G3: 33.6 Kbps  
G3: 14.4 Kbps

### Compression Method

MH, MR, MMR, JBIG

### Resolution (dpi)

400 x 400, 200 x 400, 200 x 200, 200 x 100

### Sending/Recording Size

Statement-R to 11" x 17"

### Fax Memory

Up to 30,000 Pages

### Speed Dials

Max. 200

### Group Dials/Destinations

Max. 199 Dials

### Sequential Broadcast

Max. 256 Addresses

### Memory Backup

Yes

### Fax Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's Name (TTI), Select Line, Selecting the Telephone Line, Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Detect Feeder Multi Sheet Feed

## Store Specifications

### Mail Box (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

### Advanced Box

Communication Protocol: SMB or WebDAV  
Supported  
Client PC: Windows (Windows 7/8.1/10)  
Concurrent Connections (Max.)  
SMB: 64  
WebDAV: 3 (Active Sessions)

### Advanced Box Available Disc Space

Approx. 16 GB (Standard HDD)  
Approx. 480 GB (With Optional 1 TB HDD)

### Advanced Box Features

Authentication for Advanced Box Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support

### Memory Media

Standard: USB

## Security Specifications

### Authentication

Standard: Universal Login Manager, uniFLOW Online Express,<sup>16</sup> User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in uniFLOW  
Optional:

### Data

Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated), Verify System at Startup  
Optional: Hard Disk Drive Mirroring, Hard Disk Drive removal, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

### Network

Standard: Encrypted Secure Print, IP/Mac Address Filtering, IPsec, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME, SIEM Integration

### Document

Standard: Secure Watermark, Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Digital Signature  
Optional: User Signature, Document Scan Lock

## Environmental Specifications

### Operating Environment

Temperature: 50 to 86° F  
Humidity: 20 to 80% RH (Relative Humidity)

## Power Requirements

C5560iIII/  
C5550iIII: 120-127V AC 60 Hz,11.5 A  
C5540iIII/  
C5535iIII: 120-127V AC,60 Hz,10 A

### Plug (Main Unit)

C5560iIII/  
C5550iIII: NEMA 5-20P  
C5540iIII/  
C5535iIII: NEMA 5-15P

### Power Consumption

Maximum: Approx. 1,800 W  
Standby: Approx. 65.2 W<sup>17</sup>  
Sleep Mode: Approx. 0.8 W<sup>18</sup>  
Typical Electricity Consumption (TEC) Rating:  
3.2 kWh (iR ADV C5560i III)  
2.5 kWh (iR ADV C5550i III)  
2.0 kWh (iR ADV C5540i III)  
1.6 kWh (iR ADV C5535i III)

### Standards

ENERGY STAR® Certified  
Rated EPEAT® Gold<sup>3</sup>

## Consumables

### Toner

GPR-55 Toner<sup>19</sup>

### Toner Yield (Estimated @ 5% Coverage)

Black: 69,000 Images  
Color (C,M,Y): 60,000 Images

<sup>1</sup> Subscription to a third-party cloud service required. Subject to third-party cloud service providers' terms and conditions.

<sup>2</sup> Requires additional option.

<sup>3</sup> For current EPEAT rating (Gold/Silver/Bronze), please visit [www.epeat.net](http://www.epeat.net).

<sup>4</sup> Some types of tracing paper cannot be used.

<sup>5</sup> Time from device power-on to when copy jobs can be programmed with Quick Start Up mode.

<sup>6</sup> Time from exiting Sleep mode to when printing is operational.

<sup>7</sup> Time from device power-on to when key operation can be performed on the touch screen.

<sup>8</sup> Includes main unit and either Cassette Feeding Unit-AM1, High Capacity Cassette Feeding Unit-A1, or Cabinet Type-N.

<sup>9</sup> Includes main unit, consumables, and Cassette Feeding Unit-AM1.

<sup>10</sup> PDF print from Web sites is supported.

<sup>11</sup> EPS can be printed directly only from the Remote User Interface.

<sup>12</sup> For more information, including compatibility, please visit <https://www.usa.canon.com/mobile-app>.

<sup>13</sup> Requires the optional PCL International Font Set-A1.

<sup>14</sup> Requires the optional Barcode Printer Kit-D1.

<sup>15</sup> Other operating systems and environments including AS/400, UNIX, Linux and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.

<sup>16</sup> No charge for this solution; however activation is required.

<sup>17</sup> Reference Value (measured one unit).

<sup>18</sup> 0.8 W Sleep mode not available in all circumstances due to certain settings.

<sup>19</sup> GPR-55L Toner also available for Color (C, M, Y). Yield (estimated @ 5% coverage) is 26,000 images.

For detailed specifications and a comprehensive list of optional accessories, see the imageRUNNER ADVANCE C5500 III Series Specifications document.

USA.CANON.COM/SIMPLYADVANCED



As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Canon, imageRUNNER, imageWARE, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of its features will prevent security issues. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. All other referenced product names and marks are trademarks of their respective owners. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Product shown with optional accessories. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors. ©2019 Canon U.S.A., Inc. All rights reserved.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.

0216W214  
0219-iRA5500IIISRSB-7M-DIH



UFP UNIFIED FIRMWARE PLATFORM



CANON GENUINE TONER, CARTRIDGE & PARTS

